



WWW.GOQ.KR

MODEL : GOQ 3 LED  
(WHITE)\_SPECTRUM  
2835\_10,000K



### < Characteristic >

Most Preferred Best seller LED module : CE, UL, RoHS Certified

Power Consumption : 1.08W

LED provided by SAMSUNG ( **LED : 2835 Type** )

SMD LED mounted : Made in Korea

LED Driver : Constant Voltage Driving System

Max. 50 modules in series

Design of a new and unique CAP TYPE Optical Lens

Each unit can be used to cut.

Best Viewing Angle : **170°**

### < Enhanced Function >

Stylish Appearance design : FROSTED TYPE of Optical Lens


Design for Humid & Waterproof : IP68

Easy Installation & Maintenance

### < Applications >

- \* Narrow size Channel letters
- \* Flex light Box illumination
- \* Duplex light Box illumination


## < Dimension >



## < Specification >

Item	Value	Unit
Product No.	GOQ 3 LED(WHITE)_SPECTRUM 2835	
LED	<b>2835 Type(2.8 X 3.5 X 0.65 mm)</b>	
Power Consumption	1.08	Watt
Input Voltage	12	VDC
Input Current	95	mA
View Angle	170	°
Luminous intensity	90	lm(Typ.)
CRI	75	%
Module Pitch	45	mm
Size	66 X 15 X 10.5	mm
Weight	8	g
Max. in Series	50	EA
Operating Temp	- 30 ~ 60	°C
Storage Temp	- 30 ~ 70	°C
Waterproof	IP68	
Cable	UL, 20AWG 300V/80°C	
Case materials	UL, ABS, HB-class	
Lens materials	UL, SAN, HB-class	

# < LED Specification >




## Absolute Maximum Ratings

Item	Symbol	Rating	Unit	Condition
Operating Temperature	$T_a$	-40 ~ +85	°C	-
Storage Temperature	$T_{stg}$	-40 ~ +100	°C	-
LED Junction Temperature	$T_j$	110	°C	-
Forward Current	$I_F$	150	mA	-
Peak Pulsed Forward Current	$I_{FP}$	300	mA	Duty 1/10, pulse width 10 ms
Assembly Process Temperature	-	260 <10	°C s	-

## Characteristics

Item	Unit	Nominal CCT (K)	CRI (R <sub>a</sub> ) Min.	Rank	Bin	Min.	Typ.	Max.	cd.
Forward Voltage (V <sub>F</sub> )	V	CCT	80	BA	A2	2.9	-	3.0	-
					A3	3.0	-	3.1	-
					A4	3.1	-	3.2	-
					A5	3.2	-	3.3	-
					A6	3.3	-	3.4	-
					S1	45.0	50.0	55.0	13.0~14.5
Luminous Flux (Φ <sub>v</sub> )	lm	10000	75	A0	S2	50.0	55.0	60.0	14.5~16.0
					S3	55.0	60.0	65.0	16.0~
					-	-	-	-	-
Reverse Voltage (@ 10 uA)	V	-	-	-	-	10.0	-	-	-
Special CRI (R9)	-	-	-	-	-	0	-	-	-
Thermal Resistance (junction to solder point)	°C/W	-	-	-	-	-	24	-	-
Beam Angle	°	-	-	-	-	-	120	-	-

## Spectrum (T<sub>s</sub>=25°C)



## Radiation Characteristics

