

We BRIGHTEN Your BRANDS

SloanLED SE

Maximum efficiency, low cost solution

- Newest technology with 3 chips in one LED for brighter performance in a small package
- Optimal for applications 5" in depth
- Maximum efficiency at price point

SPECIFICATIONS

Part number 701269-6WSK1-MB

Dimensions L × W × H 0.85 in × 0.45 in × 0.28 in

Viewing angle 120°

LEDs per module 1

Modules per foot 2.5

Operating temperature -40° C to +70° C

Power per module 0.43 W

Efficacy 108 lm/W

Power capacity 125 modules (50 ft) per

SloanLED 60 W 12 VDC power supply

Fastening Peel-n-stick

Packaging 20 ft (50 modules) per tray, 10 trays per carton

Color temperature 6500 K

Lumens per module 46



For photobiological compliance, the illuminance Ethr at RG1/RG2 border is 813 lux.

SloanLED channel letter products are covered by US and foreign patents pending and covered by one or more of the following US patents issued: 6,932,495, 7,160,140, 7,241,031, 7,520,771, 7,931,386 and European Patent No. 1756471

SloanLED Headquarters
5725 Olivas Park Drive • Ventura, California 93003
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.
Overslagweg 7 • 2645 EK Delfgauw • The Netherlands
+31 88 12 44 900 • Europe@SloanLED.com

SloanLED.com

© 2017 SloanLED Rev A 2017-01-06

 **SloanLED®**
Leaders in LED Technology