

## Commercial Solutions Division

# 3M™ Graffiti Remover System

## Product Description

3M™ Graffiti Remover System is designed to remove most common types of graffiti from 3M™ Scotchgard™ Graphic & Surface Protection Film Series 8991, 8993 and 8995.

Graffiti Remover System is a pH-neutral, almost colourless liquid which is free from aromatic hydrocarbons.

Product Line	Graffiti Remover	1 litre
--------------	------------------	---------

## Product Characteristics

These are indicative values for unprocessed products.  
Contact your 3M representative for a custom specification.

### Physical & Application

Application temperature (minimum air and substrate)	+10°C
--	-------

Service temperature	+10°C to +40°C
---------------------	----------------

Substrate type	3M™ Scotchgard™ Graphic & Surface Protection Film Series 8991, 8993, 8995, ceramic, brick, plaster, glass, concrete, stone, metal
----------------	---

The values above are the results of illustrative lab test measurements and shall not be considered as a commitment from 3M.

### Storage

Shelf life	Use within two years from the date of manufacture on the sealed original box. Use within one year after opening the box.
------------	---

Storage conditions	+4°C to +40°C, out of sunlight, original container in clean and dry area.
--------------------	---

The shelf life as defined above remains an indicative and maximum data, subject to many external and non-controllable factors. It may never be interpreted as warranty.

### Flammability

Flammability standards are different from country to country. Ask your local 3M contact for details, please.

## Special Information

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information and follow the manufacturers' instructions for safe operation.

Follow all recommended safety procedures as laid down in the Safety Data Sheet on the website [www.3Mgraphics.com](http://www.3Mgraphics.com).

Repaired or re-sprayed paint surfaces may be adversely effected by cleaning solutions. Customers are advised to test the 3M Graffiti Remover System on a discreet area of paint work which is the same as the eventual application surface prior to use. 3M does not accept liability for any damage to such surfaces.

## Usage Details

Apply 3M Graffiti Remover System on 3M™ Scotchgard™ Graphic & Surface Protection Film Series 8991, 8993, 8995 with a paintbrush, roller, rag or sponge. Allow 3M Graffiti Remover System to dry 5 to 10 minutes after application. Wipe off the surface with a rag and rinse with water.

## Limitations of End Uses

3M specifically does not recommend or warrant the following uses, but please contact us to discuss your needs to recommend other products.

Use on plastic and PVC is not recommended.

## Remarks

Important notice	<p>This bulletin provides technical information only.</p> <p>All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.</p> <p>Before using, the user must determine the suitability of the product for its required or intended use, and the user assumes all risk and liability whatsoever in connection therewith.</p>
Additional information	<p>Visit the web site of your local subsidiary at <a href="http://www.3Mgraphics.com">www.3Mgraphics.com</a> for getting:</p> <ul style="list-style-type: none"><li>- a complete product overview about materials 3M is offering</li></ul>



**Commercial Solutions Division**  
Hermeslaan 7  
1831 Diegem, Belgium

Responsible for this technical bulletin

3M Deutschland GmbH  
Carl-Schurz-Str. 1  
41453 Neuss, Germany

3M and Scotchguard are trademarks of 3M Company. All other trademarks are the property of their respective owners.

The use of trademark signs and brand names in this bulletin is based upon US standards. These standards may vary from country to country outside the USA.