

Hot air tool - Professional Line

HG 2120 E carwrapper-edition

EAN 4007841 008024
Article number 008024



CE



VDE

Function description

Experts in vehicle wrapping. Electronically controlled hot air tool HG 2120 E with 7.5 m cable. 2200 W, infinitely adjustable temperature from 80 – 630 °C, airflow rate adjustable from 150 – 500 l/min in 3 stages.

Technical specifications

Temperature	80 – 630 °C
Airflow rate	150 – 500 l/min
Temperature setting	Continuous
Settings made via	Thumbwheel
Temperature display	Thumbwheel with labelled settings
Airflow control	Settings
Programming function	No
Loc function	No
Residual heat indicator	No
Cool function	No
Motor, type	Brush motor
Heating element	Ceramic heating element
Mains power supply	220 – 230 V / 50 – 60 Hz
Function, hanger	Yes
Function, life expectancy, motor	750 h

Function, life expectancy, heating element	600 h
Replaceable heating element	No
Restart protection	No
Temperature scanner	Yes
Fine dust filter	No
Thermal cut-out	Yes
Thermostat	No
ESD	No
Nozzle receiver, type	34
Cord length	7.5 m
Dimensions (L x W x H)	253 x 87 x 200 mm
PU1, net weight	1,191 kg
Manufacturer's Warranty	1 year
PU1, EAN	4007841008024
Output	2200 W

Hot air tool - Professional Line

HG 2120 E carwrapper-edition

EAN 4007841 008024
Article number 008024



Accessories

EAN 4007841 071219	HDPE plastic welding rod
EAN 4007841 073411	PP plastic welding rod
EAN 4007841 073114	PVC plastic welding rod
EAN 4007841 074210	ABS plastic welding rod
EAN 4007841 009601	Flexible hot air tool stand with suction pad foot
EAN 4007841 014919	Temperature scanner HL Scan
EAN 4007841 009595	Flexible hot air tool stand with magnetic foot
EAN 4007841 075569	12-piece hot-air accessory kit
EAN 4007841 053963	Hot Air Tool Guard Cage HL 1820 S - HG 2320 E