



### Beam Angle

### Features and Benefits

- Cuttable every 1 module
- Edge lighting up-to 2 meters
- CE directives compatible
- High efficacy >100lm/W
- DC 12V
- Clean lighting
- IP 20
- CRI 80

### Technical Specifications

Operating Temperature	-30°C ~ +60°C	PCB Material	Aluminum	Finishing	UV Cured Adhesive	Adhesive Tape	3M Foam
Storage Temperature	-30°C ~ +60°C	Optics	Optical PMMA	Lifetime Tm21	>60.000 Hours	Packaging	240 Modules / Box

### Edgebar 18x Series

#### 18x 18W

#### 18x 25W

	18x 18W			18x 25W		
Power	18,00 W			25,00 W		
Input Voltage	12V DC			12V DC		
LED Quantity	18			18		
Cutting Interval	55mm - Single LED			55mm - Single LED		
Beam Angle	15° x 45°			15° x 45°		
Length x Width x Depth	990 x 25,5 x 15mm			990 x 25,5 x 15mm		
60W Power Supply Loading	6 *			3,5 *		
	Colors	Lumen	Lumen / W	Colors	Lumen	Lumen / W
	10.000K	2000	100	10.000K	2500	100
	6.500K	2000	100	6.500K	2500	100
	3.000K	2000	100	3.000K	2500	100

### Socket Connection (2 Module Connection)

NOTES: CCT Tolerance +-7%  
Lumen Values Tolerance Vary +-10%  
Special Power Options are available Upon Request  
\* %15 driver power-free space has been added to 60W driver