



Add stunning neon-like appeal and increased awareness to any building with this patented LED-based rigid tubing system.

Completely assembled and sealed tubes are ready for installation.

ColorLINE offers our brightest tubing light output, a neon-like profile, and innovative lit, mitered corners.

- Daytime color when non-illuminated
- Slim profile similar to standard neon
- High impact acrylic: UV stable, hydrocarbon insensitive, and non-fading
- Can be factory bent to minimum 9.75" radius
- Convenient, weatherproof connectors between sections

Can be cut in the field



Classic appeal.

ColorLINE adds the classic appeal and nostalgia of neon while delivering the high-efficiency, long life, and dependability of LED technology. Retaining its hue in the daytime to add color and distinction to architectural forms, ColorLINE handles straight lines and gentle curves with ease with standard product and in-field bends. For jobs requiring more customization, ColorLINE may be factory bent to a minimum 9.75" radius.

There's no substitute for quality.

Other LED manufacturers use cheaper components and maximize the potential brightness of their products at the expense of longevity; overdriving the LEDs for instant gratification while sacrificing sustainability and endurance. SloanLED uses the highest caliber components in order to offer you a superior product with the longest lifespan.



For more information on our Border Tubing & Accent collection of products, visit SloanLED.com.

Our true colors shine through.

Successful relationships are built and maintained on trust and reliability, which is why SloanLED border tube products and power supplies are backed by our 5 year product and labor warranty. From industry-leading customer care to full layout services and a bill of materials per location, we're your partner every step of the way.



ColorLINE

Specifications

Dimensions	. Width
Factory bends	. 9.75" radius (radial and flat bend)
Approx. cut increments	.2.4"
In-field bends	. Radial bend 19 ft Flat bend 6 ft
Operating temperature	40°C to +70°C
Protection class	.IP66
Binning	. MacAdam Step 3*
Power per foot	. 2.28 W
Power capacity	. 24 ft per SloanLED 60 W 12 VDC power supply
Colors	. Colors retain hue when non-illuminated (See "Unlit Product Color Chart" for Pantone color equivalents)
Mounting	Dual-position mounting clips (400381-25) orient in two directions

Color	Lumens per ft	
Red	28.01	
Orange	35.82	
Yellow	23.26	
Green	21.97	
Blue	6.94	
White (6500 K)	49.26	
Warm White (3500 K)	49.20	









- White (P/N 701800-W-X) and Warm White (P/N 701800A-WW-X) only.
- "Unlit Product Color Chart" provided as a courtesy to give a general idea of product color. Colors in chart not printed using Pantone inks and may vary from actual Pantone number/color. For an accurate representation of product color, a Pantone Color Guide book should be used, or order a sample part. For more information on Pantone, visit Pantone.com.

Power Supply Capacity

12 VDC Power supply*	Maximum ft
20 W	8
60 W	24
2×60W	2 x 24
Power used perft in Watts	2.28 W


Configured for Class 2 Output.

NOTE: When mixing modules of different sizes/colors or various products on the same power supply, simply add all the power requirements for the respective footages of each product. Then choose appropriate power supplies to provide adequate power output. The actual number of power supplies needed may vary based on how the materials are distributed across the project.

Unlit product color chart[†]

Red PANTONE 485 C	Orange PANTONE 151 C	Yellow PANTONE 3975 C
Green PANTONE 355 C	Blue PANTONE 2935 C	

Accessories



Color	Inside corner	Outside corner	Step corner
Red, Orange, Yellow, Green, Blue	701800D-IC-Color	701800D-0C-Color	701800D-SC-Color
White (6500 K)	701800-IC-W	701800-0C-W	701800-SC-W
Warm White (3500 K)	701800A-IC-WW	701800A-0C-WW	701800A-SC-WW

Joint covers

701807

Snap-on, frosted joint covers for clean finish Illuminated mitered corners



Mounting clip 400381-25



Outside corner Inside Step corner

ColorLINE is covered by US and foreign patents pending and covered by the following US patents issued: 6,776,504, 6,969,179, and 7,192,157

Ordering information

Color	Part number
Red	701800D-R- X
Orange	701800D-0- X
Yellow	701800D-Y- X
Green	701800D-G- X
Blue	701800D-B- X
White (6500 K)	701800-W- X
Warm White (3500 K)	701800A-WW- X

Code	Item description	Actual length
2	2-ft Tube	24.66"
4	4-ft Tube	48.66"
6	6-ft Tube	72.66"
8	8-ft Tube	96.66"

NOTE: $\mathbf{X} = \text{desired length}$. See table above for length codes.

SloanLED Europe b.v.

Argonstraat 110, 2718 SN Zoetermeer, NL +31 88 12 44 900 • europe@SloanLED.com

SloanLED Headquarters

3490 Venture Dr., San Angelo, TX, USA 325 227 4577 • info@SloanLED.com











Specifications subject to change without notice.

