

PosterBOX™ ID

High-performance light box illumination
for interior signage and POP applications

Specifications

Part number	Short.....	701946-6WSNP1
	Long.....	701946-6WLN1P1
Dimensions L × W × H	Short.....	8.9 in × 1.1 in × 0.62 in (225.0 mm × 27.5 mm × 15.7 mm)
	Long.....	19.5 in × 1.1 in × 0.62 in (495.3 mm × 27.5 mm × 15.7 mm)
LEDs per assembly	Short.....	3
	Long.....	6
Operating temperature	-40° C to +40° C	
Locating rating	Indoor use only	
Power per assembly	Short.....	7.2 W
	Long.....	14.0 W
Optional dimming	PWM (Pulse width modulation, SloanLED Universal LED Wireless Dimmer 601115)	
Efficacy	Short.....	118 lm/W
	Long.....	121 lm/W
Power capacity	Per SloanLED 100 W 24 VDC power supply	
	Short.....	Maximum of 12 units
	Long.....	Maximum of 6 units
Fastening	Peel-n-stick and mechanical	
Packaging	Six (6) assemblies per bag, 5 bags per carton	
Color temperature	6500 K	
Lumens per assembly	Short.....	850
	Long.....	1,700



Power Supply Capacity

24 VDC power supply	Max. units per power supply	
	Short	Long
100 W Power Supply	12	6
300 W Power Supply	3 × 12	3 × 6
Power used per unit in Watts	7.2 W	14.0 W



The SloanLED PosterBOX™ product family is licensed by Signify (formerly Philips Lighting) in relation to the following patents: North America: US7841733. Europe: EP1938298, NL1030161, NL2000273, DE202006020673.6. Asia: CN101300616. PosterBOX products are licensed under Signify's Enabled program when bought as a PosterBOX lighting kit solution including a SloanLED power supply. Final application in which PosterBOX lighting kit solution is installed is covered by SloanLED's licensing agreement with Signify and free from any further royalties relating to the patents listed above.

SloanLED Headquarters

5725 Olivas Park Drive, Ventura, CA, USA
805.676.3200 • info@SloanLED.com

SloanLED Europe b.v.

Argonstraat 110, 2718 SN Zoetermeer, NL
+31 88 12 44 900 • europe@SloanLED.com



SloanLED.com



Visit product page
for details.

